



850 SOLVENT

PRODUCT BULLETIN



www.CASSpolymers.com
31200 Stephenson Hwy

800.344.7776
Madison Heights MI 48071

ADTECH@CASSpolymers.com
Ph 248.588.2270 Fax 248.588.5909

DESCRIPTION

850 Solvent was formulated for use with ADTECH FinalFair 865 epoxy system. This solvent maintains the FinalFair 865 overall physical properties and cures to a tack-free, sandable surface. 850 Solvent is an ideal selection for making a sprayable top coat for finish fairing of aluminum or fiberglass yachts.

HANDLING CHARACTERISTICS @ 25°C/77°F

Physical State.....	Liquid
Specific Gravity	0.85
Density	7.1 lbs/gal
Shelf Life (in original unopened container)	2 years

Keep container closed when not in use. Do not store above 120°F. **For industrial use only.** Please read MSDS before use.

850 Solvent Tech/Revised 5/20/10
Supercedes116/11/08

Seller cannot anticipate all conditions under which seller's products, or the products of other manufacturers in combination with seller's products, may be used. Seller accepts no responsibility for results obtained by the application of seller's products or the safety and suitability of seller's products, either alone or in combination with other products. Users are advised to make their own test to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, seller delivers the products without warranty of any nature, stated or implied, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of said products, whether used alone or in combination with other products. Purchaser waives any claim against seller for direct, indirect, consequential or exemplary damages against seller, including without limitation, damage which may incur as a result of purchaser's use or misuse of the product or the products failure to conform to any particular specifications.