



P-29 AIR DRY PIT FILLER

SINGLE COMPONENT
GREY, WHITE & BLACK

PRODUCT BULLETIN



www.CASSpolymers.com
31200 Stephenson Hwy

800.344.7776
Madison Heights MI 48071

ADTECH@CASSpolymers.com
Ph 248.588.2270 Fax 248.588.5909

DESCRIPTION

P-29 AIR DRY PIT FILLER is a single component polymer based system which when applied, air dries to a sandable, durable surface. For use in filling porosity, surface blemishes, grinding marks as well as other surface imperfections on metal castings, sheet metal and composite parts.

P-29 is a smooth creamy paste which can be used right from the squeeze tube. No special mixing or handling is necessary and it dries to the touch within minutes after application. It has excellent adhesion when applied to metal, fiberglass, wood and other substrates. When cured it can be sanded to a feather edge and accepts virtually all finishes without any special preparation.

Typical applications include: Sealant against moisture, filling welding seams, surface glazing putty, filling pitted/porous surfaces, corrosion resistance on metal, filling pinhole voids in metal castings and filling pinhole voids in production composite parts.

HANDLING CHARACTERISTICS @ 25°C/77°F

System	Single Component
Viscosity	Creamy Smooth Paste
Density.....	12 lbs/gal
.....	1.44 gms/cc
Work Life	10-15 seconds
Tack free time	45-90 seconds
Finish Schedule (5 mil thickness).....	10 minutes
Finishing Properties	Excellent
Resin Color Choices	Grey / White / Black
Shelf Life (in original unopened containers).....	1 year
Storage Requirement.....	40°F - 80°F

P29 Tech.doc/Revised 8/18/09
Supersedes 1/10/08

Seller cannot anticipate all conditions under which seller's products, or the products of other manufacturers in combination with seller's products, may be used. Seller accepts no responsibility for results obtained by the application of seller's products or the safety and suitability of seller's products, either alone or in combination with other products. Users are advised to make their own test to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, seller delivers the products without warranty of any nature, stated or implied, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of said products, whether used alone or in combination with other products. Purchaser waives any claim against seller for direct, indirect, consequential or exemplary damages against seller, including without limitation, damage which may incur as a result of purchaser's use or misuse of the product or the products failure to conform to any particular specifications.